



Programmer's Reference

by *M Gaffiero*

gaffie@users.sourceforge.net

Class::STL::Containers

0.18

Table of Contents

Class::STL::Containers

NAME	1
SYNOPSIS	1
DESCRIPTION	2
Containers	2
Iterators	2
Algorithms	2
Utilities	2
Differences From C++/STL	3
Iterators and the end() function	3
The tree Container	3
Utilities matches, matches_ic functions	3
Container append function	3
The clone function	3
The Container to_array function	3
Container element type	3
CLASS Class::STL::ClassMembers	3
Data Member Accessor Get/Put Function	3
Class members_init() Function	3
Class clone() Function	3
Class swap() Function	3
Class::STL::ClassMembers::DataMember	4
Class::STL::ClassMembers::FunctionMember::New	4
Example	4
CLASS Class::STL::Containers	4
Exports	4
CLASS Class::STL::Containers::Abstract	4
Extends Class::STL::Element	4
new	4
clone	5
factory	5
erase	5
insert	5
pop	5
push	5
clear	5
begin	5
end	5
rbegin	6
rend	6
size	6
empty	6
to_array	6
eq	6
ne	6
operator +, operator +=	6
operator ==	6
operator !=	6
CLASS Class::STL::Containers::List	6
Extends Class::STL::Containers::Deque	7
reverse	7
sort	7
Example	7
CLASS Class::STL::Containers::Vector	7

Extends Class::STL::Containers::Abstract	7
push_back	7
pop_back	7
back	7
front	8
at	8
CLASS Class::STL::Containers::Deque	8
Extends Class::STL::Containers::Vector	8
push_front	8
pop_front	8
CLASS Class::STL::Containers::Queue	8
Extends Class::STL::Containers::Abstract	8
push	8
pop	8
back	8
front	8
CLASS Class::STL::Containers::Stack	9
Extends Class::STL::Containers::Abstract	9
push	9
pop	9
top	9
CLASS Class::STL::Containers::Tree	9
Extends Class::STL::Containers::Deque	9
to_array	9
Examples	9
CLASS Class::STL::Containers::PriorityQueue	9
Extends Class::STL::Containers::Vector	10
Element Type Class::STL::Element::Priority	10
push	10
pop	10
top	10
refresh	10
CLASS Class::STL::Algorithms	10
Exports	10
for_each	10
transform	10
count	11
count_if	11
find	11
find_if	11
copy	11
copy_backward	11
remove	11
remove_if	11
remove_copy	11
remove_copy_if	11
replace	11
replace_if	11
replace_copy	11
replace_copy_if	11
generate	11
generate_n	12
fill	12
fill_n	12
equal	12
reverse	12
reverse_copy	12
rotate	12
rotate_copy	12

partition	12
stable_partition	12
min_element	12
max_element	12
unique	12
unique_copy	12
adjacent_find	12
Examples	12
CLASS Class::STL::Utilities	13
Exports	13
equal_to	13
not_equal_to	13
greater	13
greater_equal	13
less	13
less_equal	13
compare	13
matches	13
matches_ic	13
bind1st	13
bind2nd	14
mem_fun	14
ptr_fun	14
ptr_fun_binary	14
logical_and	14
logical_or	14
multiplies	14
divides	14
plus	14
minus	14
modulus.	14
CLASS Class::STL::Iterators	14
Exports	15
new	15
p_container	15
p_element	15
distance	15
advance	15
inserter	15
front_inserter	15
back_inserter	15
first	15
next	15
last	15
prev	15
at_end	15
eq	15
ne	15
lt	15
le	15
gt	15
ge	15
cmp	15
Examples	15
SEE ALSO	16
AUTHOR	16
COPYRIGHT AND LICENSE	16

NAME

Class::STL::Containers - Perl extension for STL-like object management

SYNOPSIS

```

use stl;

# Deque container...
my $d = deque(qw(first second third fourth));
$d->push_back($d->factory('fifth'));
$d->push_front($d->factory('seventh'));
$d->pop_front(); # remove element at front.
$d->pop_back(); # remove element at back.
for_each($d->begin(), $d->end(), ptr_fun('::myprint'));

sub myprint { print "Data:", @_, "\n"; }

# Copy constructor...
my $d_copy = deque($d);

# Algorithms -- find_if()
print "Element 'second' was ",
    find_if($d->begin(), $d->end(), bind1st(equal_to(), 'second'))
    ? 'found' : 'not found', "\n";

# Algorithms -- count_if()
print "Number of elements matching /o/ = ",
    count_if($d->begin(), $d->end(), bind2nd(matches(), 'o')),
    "\n"; # prints '2' -- matches 'second' and 'fourth'

# Algorithms -- transform()
transform($d->begin(), $d->end(), $d2->begin(), ptr_fun('ucfirst'));
transform($d->begin(), $d->end(), $d2->begin(), $d3->begin(), ptr_fun_binary('::mybfun'));
sub mybfun { return $_[0] . '-' . $_[1]; }

# Function Adaptors -- bind1st
remove_if($v->begin(), $v->end(), bind1st(equal_to(), $v->back()));
# remove element equal to back() -- ie remove last element.
remove_if($v->begin(), $v->end(), bind2nd(matches(), '^fi'));
# remove all elements that match reg-ex '^fi'

# Sort list according to elements cmp() function
$v->sort();

# Queue containers -- FIFO
my $v = queue(qw(first second third fourth fifth));
print 'Back:', $v->back()->data(), "\n" # Back:fifth
print 'Front:', $v->front()->data(), "\n" # Front:first
$v->pop(); # pop element first in
$v->push($v->factory('sixth'), "\n"
print 'Back:', $v->back()->data(), "\n" # Back:sixth
print 'Front:', $v->front()->data(), "\n" # Front:second

# Iterators
for (my $i = $v->begin(); !$i->at_end(); ++$i)
{
    print "Data:", $i->p_element()->data();
}

# Iterators -- reverse_iterator
my $ri = reverse_iterator($v->iter()->first());
while (!$ri->at_end())
{
    print "Data:", $ri->p_element()->data();
    ++$ri;
}

# Inserters
my $three2one = list(qw(3 2 1));
my $four2six = list(qw(4 5 6));
my $seven2nine = list(qw(7 8 9));
my $result = list();
copy($three2one->begin(), $three2one->end(), front_inserter($result));
copy($seven2nine->begin(), $seven2nine->end(), back_inserter($result));
my $seven = find($result->begin(), $result->end(), 7);
copy($four2six->begin(), $four2six->end(), inserter($result, $seven));
# $result now contains (1, 2, 3, 4, 5, 6, 7, 8, 9);

# Vector container...
my $v = vector(qw(first second third fourth fifth));

```

```

my $e = $v->at(0); # return pointer to first element.
print 'Element-0:', $e->data(), "\n"; # Element-0:first
$e = $v->at($v->size()-1); # return pointer to last element.
print 'Element-last:', $e->data(), "\n"; # Element-last:fifth
$e = $v->at(2); # return pointer to 3rd element (idx=2).
print 'Element-2:', $e->data(), "\n"; # Element-2:third

# Priority Queue
my $p = priority_queue();
$p->push($p->factory(priority => 10, data => 'ten'));
$p->push($p->factory(priority => 2, data => 'two'));
$p->push($p->factory(priority => 12, data => 'twelve'));
$p->push($p->factory(priority => 3, data => 'three'));
$p->push($p->factory(priority => 11, data => 'eleven'));
$p->push($p->factory(priority => 1, data => 'one'));
$p->push($p->factory(priority => 1, data => 'one-2'));
$p->push($p->factory(priority => 12, data => 'twelve-2'));
$p->push($p->factory(priority => 20, data => 'twenty'), $p->factory(priority => 0, data => 'zero'));
print "\$p->size()=", $p->size(), "\n";
print "\$p->top():", $p->top(), "\n";
$p->top()->priority(7); # change priority for top element.
$p->refresh(); # refresh required after priority change.
$p->pop(); # remove element with highest priority.
print "\$p->top():", $p->top(), "\n";

# Clone $d container into $d1...
my $d1 = $d->clone();

my $d2 = deque(qw(sixth seventh eight));

# Append $d container to end of $d2 container...
$d2 += $d;

# DataMembers -- Class builder helper...
{
    package MyClass;
    use Class::STL::ClassMembers (
        qw(attrib1 attrib2), # data members
        Class::STL::ClassMembers::DataMember->new(
            name => 'attrib3', default => '100', validate => '^\d+$'), # data member with attributes
        Class::STL::ClassMembers::DataMember->new(
            name => 'attrib4', default => 'med', validate => '^(high|med|low)$'),
        Class::STL::ClassMembers::FunctionMember::New->new(), # produce class new() function
    );
}
my $c1 = MyClass->new(attrib1 => 'hello', attrib2 => 'world');
print $c1->attrib1(), " ", $c1->attrib2(), "\n"; # 'hello world'
$c1->attrib1(ucfirst($c1->attrib1));
$c1->attrib2(ucfirst($c1->attrib2));
print $c1->attrib1(), " ", $c1->attrib2(), "\n"; # 'Hello World'
$c1->attrib4('avg'); # Causes program to die with '** Function attrib2 value failed validation...'

```

DESCRIPTION

This package provides a framework for rapid Object Oriented Perl application development. It consists of a number of base classes that are similar to the C++/STL framework, plus a number of *helper* classes which provide the *glue* to transparently generate common functions, and will enable you to put your Perl application together very quickly.

The STL functionality provided consists of **containers**, **algorithms**, **utilities** and **iterators** as follows:

Containers

vector, list, deque, queue, priority_queue, stack, tree.

Iterators

iterator, bidirectional_iterator, reverse_iterator, forward_iterator.

Algorithms

find, find_if, for_each, transform, count, count_if, copy, copy_backward, remove, remove_if, remove_copy, remove_copy_if, replace, replace_if, replace_copy, replace_copy_if.

Utilities

equal_to, not_equal_to, greater, greater_equal, less, less_equal, compare, bind1st, bind2nd, mem_fun, ptr_fun, ptr_fun_binary, matches, matches_ic, logical_and, logical_or, multiplies, divides, plus, minus, modulus.

Differences From C++/STL

Most of the functions have the same arguments and return types as their STL equivalent. There are some differences though between the C++/STL and this implementation:

Iterators and the *end()* function

An *iterator* object points to a numeric position within the container, and not to an *element*. If new elements are inserted to, or removed from, a position preceding the iterator, then the iterator will point to the same *position* but to a different element.

The *end* function will return a newly constructed iterator object which will point to the *last* element within the container, unlike the C++/STL equivalent which points to *after* the last element.

The *tree* Container

This container provides a hierarchical tree structure. Each element within a *tree* container can be either a simple element or another container object. The *algorithms* and overridden *to_array* functions will traverse the tree and process all element *nodes* within the tree.

Utilities *matches*, *matches_ic* functions

These utilities provide unary functions for regular expression matching. The first or second argument will be a regular expression string. The *match_ic* provides case insensitive matching.

Container *append* function

This function and the overridden *+*, *+=* operators will combine the two containers together.

The *clone* function

This function returns a newly constructed object that is a copy of its caller object.

The Container *to_array* function

This function will return an array consisting of all element objects within the container.

Container *element* type

All containers contain collections of objects which are of type **Class::STL::Element**, or classes derived from this type. The container classes are themselves, ultimately, derived from this *element* type.

CLASS Class::STL::ClassMembers

This *helper* class can be used to generate code for various basic class functions. This module requires an import list consisting of target data member names, *Class::STL::ClassMembers::DataMember*, or *Class::STL::ClassMembers::FunctionMember* objects. When using *ClassMembers* **ALL** data members should be included in order for the generated *clone* and *swap* functions to function correctly.

The following target member functions will be generated and made available to the class:

Data Member Accessor Get/Put Function

This function will have the same name as the data member and should be used to *set* or *get* the value for the data member. Pass the value as the argument when setting the value for a data member. For *complex* data members with a **validate** attribute, a validation check will be performed when attempting to set the member value by matching the value against the *validate* regular expression string.

Class *members_init()* Function

This function should be called in the target class's *new* function after *\$self* has been blessed. It will perform the necessary data members initialisation.

Class *clone()* Function

This function will construct and return an object containing a copy of the caller object.

Class *swap()* Function

This function requires one argument consisting of an object of the same type as the caller. It will swap the caller object with this *other* object.

Class::STL::ClassMembers::DataMember

For more complex data members, this class may be used to provide additional information about the member. This information consist of: **name**, **default**, and **validate**. The **name** attribute contains the member name; the **default** attribute contains a default value for the member when initialised; the **validate** attribute consists of a regular expression string that will be used to validate the member value by matching it to this regex string.

Class::STL::ClassMembers::FunctionMember::New

By including a constructed object of this type (via the `new()` function) in the import list for **Class::STL::ClassMembers**, the **new()** function will be produced for the *caller* class.

Example

```
{
  package MyClass;
  use Class::STL::ClassMembers (
    qw(attrib1 attrib2),
    Class::STL::ClassMembers::DataMember->new(
      name => 'attrib3', default => '100', validate => '^d+$'),
    Class::STL::ClassMembers::DataMember->new(
      name => 'attrib4', default => 'med', validate => '^(high|med|low)$'),
    Class::STL::ClassMembers::FunctionMember::New->new(), # produce class new() function
  );
}
my $cl = MyClass->new(attrib1 => 'hello', attrib2 => 'world');
print $cl->attrib1(), " ", $cl->attrib2(), "\n"; # 'hello world'
$cl->attrib1(ucfirst($cl->attrib1));
$cl->attrib2(ucfirst($cl->attrib2));
print $cl->attrib1(), " ", $cl->attrib2(), "\n"; # 'Hello World'
$cl->attrib4('avg'); # Causes program to die with '** Function attrib2 value failed validation...'
```

CLASS Class::STL::Containers

Exports

vector, **list**, **deque**, **queue**, **priority_queue**, **stack**, **tree**.

CLASS Class::STL::Containers::Abstract

This is the *abstract* base class for all other container classes. Objects should not be constructed directly from this class, but from any of the derived container classes. Common functions are documented here.

Extends Class::STL::Element

new

```
container-ref new ( [ named-argument-list ] );
container-ref new ( container-ref );
container-ref new ( element [ ... ] );
container-ref new ( iterator-start [ , iterator-finish ] );
container-ref new ( raw-data [ ... ] );
```

The *new* function constructs an object for this class and returns a blessed reference to this object. All forms accept an optional *hash* containing any of the following named arguments: *data_type*. The *data_type* defines the class type of element objects that the container will hold.

The second form is a *copy constructor*. It requires another container reference as the argument, and will return a copy of this container.

The third form requires one or more element refs as arguments. These elements will be copied into the newly constructed container.

The fourth form requires one *start* iterator and an optional *finish* iterator. All the element objects with, and including, the *start* and *finish* (or *end* if not specified) positions will be copied into the newly constructed container.

The fifth form accepts a list of raw data values. Each of these values will be stored inside a **Class::STL::Element** object constructed by the container's *factory* function, with the element's *data* member containing the raw data value.

clone

Returns a newly constructed object which is identical to the calling (this) object.

factory

element-ref factory (%attributes);

The *factory* function constructs a new element object and returns a reference to this. The type of object created is as specified by the *element_type* container attribute. The *attributes* argument consists of a hash and is passed on to the element class *new* function. Override this function if you want to avoid the 'eval' call.

erase

iterator erase (iterator-start [, iterator-finish]);

The *erase* function requires one starting iterator and an optional finish iterator as arguments. It will delete all the elements in the container within, and including, these two iterator positions. The *erase* function returns an iterator pointing to the element following the last deleted element.

insert

void insert (position, iterator-start, iterator-finish);

void insert (position, iterator-start);

void insert (position, element [, ...]);

void insert (position, size, element);

The first form will insert copies of elements within the *iterator-start* and *iterator-finish* positions before *position*.

The second form will insert copies of elements within the *iterator-start* and *end* positions before *position*.

The third form will insert the element, or elements (*not copies*) before *position*.

The fourth form will insert *size* copies of *element* before *position*.

pop

void pop ();

The *pop* function requires no arguments. It will remove the element at the *top* of the container.

push

void push (element [, ...]);

The *push* function requires one or more arguments consisting of elements. This will append the element(s) to the end of the container.

clear

void clear ();

This function will delete all the elements from the container.

begin

iterator-ref begin ();

The *begin* function constructs and returns a new iterator object which points to the *front* element within the container.

end

iterator-ref end ();

The *end* function constructs and returns a new iterator object which points to the **back** element within the container. **Note that, unlike C++/STL, this object points to the last element and not *after the last element*.

rbegin

iterator-ref rbegin ();

The *rbegin* function is the reverse of the *begin* function — the newly constructed iterator points to the last element.

rend

iterator-ref rend ();

The *rend* function is the reverse of the *end* function — the newly constructed iterator points to the first element.

size

int size ();

The *size* function requires no arguments. It will return an integer value containing the number of elements in the container.

empty

bool empty ();

This function returns '1' if the container is empty (ie. contains no elements), and '0' if the container contains one or more elements.

to_array

array to_array ();

The *to_array* function returns an array containing the elements (references) from the container.

eq

bool eq (container-ref);

The *eq* function compares the *elements* in this container with the *elements* in the container referred to by the argument *container-ref*. The elements are compared using the element *eq* function. The function will return '1' if both containers contain the same number of elements and all elements in one container are equal to, and in the same order as, all elements in the *container-ref* container.

ne

bool ne (container-ref);

Inverse of *eq* function.

operator +, operator +=

Append containers.

operator ==

Containers equality comparison.

operator !=

Containers non-equality comparison.

CLASS Class::STL::Containers::List

A list container can have elements pushed and popped from both ends, and also inserted at any location. Access to the elements is sequential.

Extends *Class::STL::Containers::Deque*

reverse

void reverse ();

The *reverse* function will alter the order of the elements in list by reversing their order.

sort

void sort ();

The *sort* function will alter the order of the elements in list by sorting the elements. Sorting is done based on the elements *cmp* comparison function.

Example

```
use stl;

# Construct the list object:
my $list = list(qw( first second third fourth fifth));

# Display the number of elements in the list:
print "Size:", $list->size(), "\n"; # Size:5

# Reverse the order of elements in the list:
$list->reverse();

# Display the contents of the element at the front of the list:
print 'Front:', $list->front(), "\n";

# Display the contents of the element at the back of the list:
print 'Back:', $list->back(), "\n";

# Display the contents of all the elements in the list:
for_each($list->begin(), $list->end(), MyPrint->new());

# Return an array of all elements-refs:
my @arr = $list->to_array();

# Delete all elements from list:
$list->clear();

print "Size:", $list->size(), "\n"; # Size:0
print '$list container is ',
    $list->empty() ? 'empty' : 'not empty', "\n";

# MyPrint Unary Function -- used in for_each() above...
{
    package MyPrint;
    use base qw(Class::STL::Utilities::FunctionObject::UnaryFunction);
    sub function_operator
    {
        my $self = shift;
        my $arg = shift;
        print "Data:", $arg->data(), "\n";
    }
}
```

CLASS Class::STL::Containers::Vector

A vector allows for random access to its elements via the *at* function.

Extends *Class::STL::Containers::Abstract*

push_back

void push_back (element [, ...]);

The *push_back* function requires one or more arguments consisting of elements. This will append the element(s) to the end of the *vector*.

pop_back

void pop_back ();

The *pop_back* function requires no arguments. It will remove the element at the *top* of the *vector*.

back

element-ref back ();

The *back* function requires no arguments. It returns a reference to the element at the *back* of the *vector*.

front

The *front* function requires no arguments. It returns a reference to the element at the *front* of the *vector*.

at

element-ref at (index);

The *at* function requires an *index* argument. This function will return a reference to the element at the location within the *vector* specified by the argument *index*.

CLASS Class::STL::Containers::Deque

A double-ended container. Elements can be *pushed* and *popped* at both ends.

Extends *Class::STL::Containers::Vector*

push_front

void push_front (element [, ...]);

The *push_front* function requires one or more arguments consisting of elements. This will insert the element(s) to the front of the *deque*.

pop_front

void pop_front ();

The *pop_front* function requires no arguments. It will remove the element at the *front* of the *deque*.

CLASS Class::STL::Containers::Queue

A queue is a FIFO (first-in-first-out) container. Elements can be *pushed* at the back and *popped* from the front.

Extends *Class::STL::Containers::Abstract*

push

void push (element [, ...]);

The *push* function requires one or more arguments consisting of elements. This will append the element(s) to the back of the *queue*.

pop

void pop ();

The *pop* function requires no arguments. It will remove the element at the *front* of the *queue*. This is the earliest inserted element.

back

element-ref back ();

The *back* function requires no arguments. It returns a reference to the element at the *back* of the *queue*. This is the element last inserted.

front

element-ref front ();

The *front* function requires no arguments. It returns a reference to the element at the *front* of the *queue*. This is the earliest inserted element.

CLASS Class::STL::Containers::Stack

A stack is a LIFO (last-in-first-out) container. Elements can be *pushed* at the top and *popped* from the top.

Extends *Class::STL::Containers::Abstract*

push

void push (element [, ...]);

The *push* function requires one or more arguments consisting of elements. This will append the element(s) to the top of the *stack*.

pop

void pop ();

The *pop* function requires no arguments. It will remove the element at the *top* of the *stack*. This is the last inserted element.

top

element-ref top ();

The *top* function requires no arguments. It returns a reference to the element at the *top* of the *stack*. This is the last inserted element.

CLASS Class::STL::Containers::Tree

A tree is a hierarchical structure. Each element within a *tree* container can be either a simple element or another container object. The overridden *to_array* function will traverse the tree and return an array consisting of all the *nodes* in the tree.

Extends *Class::STL::Containers::Deque*

to_array

array to_array ();

The overridden *to_array* function will traverse the tree and return an array consisting of all the element *nodes* in the tree container.

Examples

```
# Tree containers; construct two trees from
# previously constructed containers:
my $t1 = tree($l1);
my $t2 = tree($l2);

# Construct a third tree:
my $tree = tree();

# Add other tree containers as elements to this tree:
$tree->push_back($tree->factory($t1));
$tree->push_back($tree->factory($t2));

# Search for element ('pink') in tree:
if (my $f = find_if($tree->begin(), $tree->end(), bind1st(equal_to(), 'pink')))
    print "FOUND:", $f->data(), "\n";
} else {
    print "'pink' NOT FOUND", "\n";
}

# Traverse tree returning all element nodes:
my @tarr = $tree->to_array();
```

CLASS Class::STL::Containers::PriorityQueue

A priority queue will maintain the order of the elements based on their priority, with highest priority elements at the top of the container. Elements contained in a priority queue must be of the type, or derived from, *Class::STL::Element::Priority*. This element type contains the attribute *priority*, and needs to have its value set whenever an object of this element type is constructed.

Extends *Class::STL::Containers::Vector*

Element Type *Class::STL::Element::Priority*

push

void push (element [, ...]);

The *push* function requires one or more arguments consisting of elements. This will place the element(s) in the queue according to their priority value.

pop

void pop_back ();

The *pop* function requires no arguments. It will remove the element with the highest priority.

top

element-ref top ();

The *top* function requires no arguments. It returns a reference to the element with the highest priority.

refresh

void refresh ();

The *refresh* function should be called whenever the priority value for an element has been order. This will update the ordering of the elements if required.

CLASS *Class::STL::Algorithms*

This module contains various algorithm functions.

Exports

remove_if, find_if, for_each, transform, count_if, find, count, copy, copy_backward, remove, remove_copy, remove_copy_if, replace, replace_if, replace_copy, replace_copy_if, generate, generate_n, fill, fill_n, equal, reverse, reverse_copy, rotate, rotate_copy, partition, stable_partition, min_element, max_element, unique, unique_copy, adjacent_find

The **Algorithms** package consists of various *static* algorithm functions.

The *unary-function* / *binary-function* argument must be derived from

Class::STL::Utilities::FunctionObject::UnaryFunction and

Class::STL::Utilities::FunctionObject::BinaryFunction respectively. Standard utility functions are provided in the *Class::STL::Utilities* module. A function object contains the function *function_operator*. This *function_operator* function will, in turn, be called by the algorithm for each element traversed. The algorithm will pass the element reference as the argument to the *function_operator* function.

for_each

void for_each (iterator-start, iterator-finish, unary-function);

The *for_each* function will traverse the container starting from *iterator-start* and ending at *iterator-finish* and execute the *unary-function* with the element passed in as the argument.

transform

void transform (iterator-start, iterator-finish, iterator-result, unary-function);

void transform (iterator-start, iterator-finish, iterator-start2, iterator-result, binary-function);

The *transform* functions has two forms. The first form will traverse the container starting from *iterator-start* and ending at *iterator-finish* and execute the *unary-function* with the element passed in as the argument, producing *iterator-result*.

The second form will traverse two containers with the second one starting from *iterator-start2*. The *binary-function* will be called for each pair of elements. The resulting elements will be placed in *iterator-result*.

count

```
int count ( iterator-start, iterator-finish, element-ref );
```

count_if

```
int count_if ( iterator-start, iterator-finish, unary-function );
```

The *count_if* function will traverse the container starting from *iterator-start* and ending at *iterator-finish* and return a count of the elements that evaluate to true by the *unary-function*.

find

```
iterator-ref find ( iterator-start, iterator-finish, element-ref );
```

find_if

```
iterator-ref find_if ( iterator-start, iterator-finish, unary-function );
```

The *find_if* function will traverse the container starting from *iterator-start* and ending at *iterator-finish* and return an *iterator* pointing to the first element that evaluate to true by the *unary-function*. If no elements evaluates to true then 'o' is returned.

copy

```
void copy ( iterator-start, iterator-finish, iterator-result );
```

copy_backward

```
void copy_backward ( iterator-start, iterator-finish, iterator-result );
```

remove

```
void remove ( iterator-start, iterator-finish, element-ref );
```

remove_if

```
void remove_if ( iterator-start, iterator-finish, unary-function );
```

The *remove_if* function will traverse the container starting from *iterator-start* and ending at *iterator-finish* and remove the elements that evaluate to true by the *unary-function*.

remove_copy

```
void remove_copy ( iterator-start, iterator-finish, iterator-result, element-ref );
```

remove_copy_if

```
void remove_copy_if ( iterator-start, iterator-finish, iterator-result, unary-function );
```

replace

```
void replace ( iterator-start, iterator-finish, old-element-ref, new-element-ref );
```

replace_if

```
void replace_if ( iterator-start, iterator-finish, unary-function, new-element-ref );
```

replace_copy

```
void replace_copy ( iterator-start, iterator-finish, iterator-result, old-element-ref, new-element-ref );
```

replace_copy_if

```
void replace_copy_if ( iterator-start, iterator-finish, iterator-result, unary-function, new-element-ref );
```

generate

```
void generate ( iterator-start, iterator-finish, generator-function );
```

generate_n

```
void generate_n ( iterator-start, size, generator-function );
```

fill

```
void fill ( iterator-start, iterator-finish, element-ref );
```

fill_n

```
void fill_n ( iterator-start, size, element-ref );
```

equal

```
bool equal ( iterator-start, iterator-finish, iterator-result [, binary-function ] );
```

reverse

```
void reverse ( iterator-start, iterator-finish );
```

reverse_copy

```
void reverse_copy ( iterator-start, iterator-finish, iterator-result );
```

rotate

```
void rotate ( iterator-start, iterator-mid, iterator-finish );
```

rotate_copy

```
void rotate_copy ( iterator-start, iterator-mid, iterator-finish, iterator-result );
```

partition

```
void partition ( iterator-start, iterator-finish, [, unary-predicate ] );
```

stable_partition

```
void stable_partition ( iterator-start, iterator-finish, [, unary-predicate ] );
```

min_element

```
iterator min_element ( iterator-start, iterator-mid [, binary-function ] );
```

max_element

```
iterator max_element ( iterator-start, iterator-mid [, binary-function ] );
```

unique

```
iterator unique ( iterator-start, iterator-finish, [, binary-function ] );
```

unique_copy

```
iterator unique_copy ( iterator-start, iterator-finish, iterator-result [, binary-function ] );
```

adjacent_find

```
iterator adjacent_find ( iterator-start, iterator-finish, [, binary-predicate ] );
```

Examples

```
use Class::STL::Containers;
use Class::STL::Algorithms;
use Class::STL::Utilities;

# Display all elements in list container '$list'
# using unary-function 'myprint' and algorithm 'for_each':
for_each($list->begin(), $list->end(), ptr_fun('::myprint'));
sub myprint { print "Data:", $_[0], "\n"; }

# Algorithms -- remove_if()
# Remove element equal to back() -- ie remove last element:
remove_if($list->begin(), $list->end(), bind1st(equal_to(), $list->back()));

# Remove all elements that match regular expression '^fi':
```

```

remove_if($v->begin(), $v->end(), bind2nd(matches(), '^fi'));

# Search for element ('pink') in tree:
if (my $f = $tree->find_if($tree->begin(), $tree->end(), bind1st(equal_to(), "pink"))) {
    print "FOUND:", $f->p_element()->data(), "\n";
} else {
    print "'pink' NOT FOUND", "\n";
}

```

CLASS Class::STL::Utilities

Exports

***equal_to*, *not_equal_to*, *greater*, *greater_equal*, *less*, *less_equal*, *compare*, *bind1st*, *bind2nd*, *mem_fun*, *ptr_fun*, *ptr_fun_binary*, *matches*, *matches_ic*, *logical_and*, *logical_or*, *multiplies*, *divides*, *plus*, *minus*, *modulus*.**

This module contains various utility function objects. Each object will be constructed automatically when the function name (eg. 'equal_to') is used. Each of the function objects are derived from either *Class::STL::Utilities::FunctionObject::UnaryFunction* or *Class::STL::Utilities::FunctionObject::BinaryFunction*.

equal_to

Binary predicate. This function-object will return the result of *equality* between its argument and the object *arg* attribute's value. The element's *eq* function is used for the comparison.

not_equal_to

Binary predicate. This function is the inverse of *equal_to*.

greater

Binary predicate. This function-object will return the result of *greater-than* comparison between its argument and the object *arg* attribute's value. The element's *gt* function is used for the comparison.

greater_equal

Binary predicate. This function-object will return the result of *greater-than-or-equal* comparison between its argument and the object *arg* attribute's value. The element's *ge* function is used for the comparison.

less

Binary predicate. This function-object will return the result of *less-than* comparison between its argument and the object *arg* attribute's value. The element's *lt* function is used for the comparison.

less_equal

Binary predicate. This function-object will return the result of *less-than-or-equal* comparison between its argument and the object *arg* attribute's value. The element's *le* function is used for the comparison.

compare

Binary predicate. This function-object will return the result of *compare* comparison between its argument and the object *arg* attribute's value. The element's *cmp* function is used for the comparison.

matches

Binary predicate. This function-object will return the result (true or false) of the regular expression comparison between its first argument and its second argument which contains a regular expression string.

matches_ic

Binary predicate. Case-insensitive version of the *matches* function.

bind1st

Unary function. This function requires two arguments consisting of a *binary-function-object* and a element or value argument. It will produce a *unary-function* object whose *function_operator* member will call the *binary-function* with *argument* as the first argument.

bind2nd

Unary function. This function requires two arguments consisting of a *binary-function-object* and a element or value argument. It will produce a *unary-function* object whose *function_operator* member will call the *binary-function* with *argument* as the second argument.

mem_fun

This function requires one argument consisting of the class member function name (string). It will construct an object whose *function_operator* member will require an element object to be passed as the first argument. It will call the elements's member function as specified by the *mem_fun* argument.

ptr_fun

Unary function. This function requires one argument consisting of a global function name (string).

ptr_fun_binary

Binary function. This function requires one argument consisting of global function name (string).

logical_and

Binary predicate.

logical_or

Binary predicate.

multiplies

Binary function. This function-object will return the result of *multiply* between its two element arguments. The element's *mult* function is used for the calculation. It will return a newly constructed element object containing the result.

divides

Binary function. This function-object will return the result of *division* between its two element arguments. The element's *div* function is used for the calculation. It will return a newly constructed element object containing the result.

plus

Binary function. This function-object will return the result of *plus* between its two element arguments. The element's *add* function is used for the calculation. It will return a newly constructed element object containing the result.

minus

Binary function. This function-object will return the result of *subtract* between its two element arguments. The element's *subtract* function is used for the calculation. It will return a newly constructed element object containing the result.

modulus.

Binary function. This function-object will return the result of *modulus* between its two element arguments. The element's *mod* function is used for the calculation. It will return a newly constructed element object containing the result.

CLASS Class::STL::Iterators

This module contains the iterator classes.

Exports

iterator, bidirectional_iterator, reverse_iterator, forward_iterator, ++, --, ==, !=, >=, <=, +, +=, -, -=, distance, advance, front_inserter, back_inserter, inserter.

new

p_container

Returns a reference to the container that is associated with the iterator.

p_element

This function will return a reference to the element pointed to by the iterator.

distance

Static function. This function will return the *distance* between two iterators. Both iterators must be from the same container. *Iterator-finish* must be positioned after *iterator-first*.

int distance (iterator-start, iterator-finish]);

advance

Static function. Moves the iterator forward, or backwards if size is negative.

iterator advance (iterator, size);

inserter

Static function.

iterator inserter (container, iterator);

front_inserter

Static function.

iterator front_inserter (container);

back_inserter

Static function.

iterator back_inserter (container);

first

next

last

prev

at_end

eq

ne

lt

le

gt

ge

cmp

Examples

```
# Using overloaded increment operator:
for (my $i = $p->begin(); !$i->at_end(); $i++)
{
    MyPrint->new()->function_operator($i->p_element());
}

# Using overloaded decrement operator:
for (my $i = $p->end(); !$i->at_end(); --$i)
```

```
{
    MyPrint->new()->function_operator($i->p_element());
}

# Reverse iterator:
my $ri = reverse_iterator($p->iter()->first());
while (!$ri->at_end())
{
    MyPrint->new()->function_operator($ri->p_element());
    $ri->next();
}
```

SEE ALSO

Sourceforge Project Page: <http://sourceforge.net/projects/pstl>

AUTHOR

m gaffiero, <gaffie@users.sourceforge.net>

COPYRIGHT AND LICENSE

Copyright (C) 2006 by Mario Gaffiero

This file is part of Class::STL::Containers(TM).

Class::STL::Containers is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation; either version 2 of the License, or (at your option) any later version.

Class::STL::Containers is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU General Public License for more details.

You should have received a copy of the GNU General Public License along with Class::STL::Containers; if not, write to the Free Software Foundation, Inc., 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA