```
john% xcheckmail -h sheriff
Please wait while attempt to connect to sheriff....connected
The messages from pac on sheriff are as follows:
msg.aa03130 is pending delivery to p.pat@cs.nott.ac.uk

john% xcheckmail -h sheriff -a
Please wait while attempt to connect to sheriff....connected
The messages to or from pac on sheriff are as follows:
msg.aa03130 is pending delivery to p.pat@cs.nott.ac.uk
msg.aa03140 is from  P.Pat@cs.nott.ac.uk
```

Index

#, 7
822-local, 5, 6

A
.alert, 11, 12
aliases, 19

B
/bin/mail, 26
body, 10
Boolean operators, 5

C
checking .mailfilter, 8
checkmail, 26
chkmf, 2
ckmail, 2
ckmf, 9
comment, 7
compound statement, 5
conditionals, 5
cron, 25

D
delivered, 4, 6
delivery states, 6
dirlist, 19
dl, 22
dsaptailor, 19, 22

E
else, 5
else if, 5
ETCDIR, 19
exit, 7
extra, 10

F
file, 4
flagmail, 2, 9, 11, 12
flock, 15
From, 10

H
header fields, 6

I
if, 5
ignore, 4
isoaliases, 19

L
LaTeX, 28

M
mail, 2
.mailfilter, 2, 3, 4, 5, 7, 8, 10, 13
malias, 2, 19
mlist, 2, 17, 18, 19
more, 25

P
PATH, 6
pipe, 4
print, 7
printf, 10

Q
.quipurc, 22

R
rcvstore, 7
rcvtrip, 13
regexp, 7
regular expressions, 7
resend, 2, 14

S
.signature, 14
size, 10
strip_addr, 15
strip_addr , 2
system variables, 6

T
triplog, 14
tripnote, 13
ttripnote, 14
ttyalert, 2, 9, 11, 12, 13
ttybiff, 12, 13

U
unixfile, 4
users, 19

V
variables, 6

system, 6

X xalert, 2, 9, 11, 12