IEEE P1003.2 Draft 11.2 – September 1991

Copyright © 1991 by the
Institute of Electrical and Electronics Engineers, Inc.
345 East 47th Street
New York, NY 10017, USA
All rights reserved as an unpublished work.

This is an unapproved and unpublished IEEE Standards Draft, subject to change. The publication, distribution, or copying of this draft, as well as all derivative works based on this draft, is expressly prohibited except as set forth below.

Permission is hereby granted for IEEE Standards Committee participants to reproduce this document for purposes of IEEE standardization activities only, and subject to the restrictions contained herein.

Permission is hereby also granted for member bodies and technical committees of ISO and IEC to reproduce this document for purposes of developing a national position, subject to the restrictions contained herein.

Permission is hereby also granted to the preceding entities to make limited copies of this document in an electronic form only for the stated activities.

The following restrictions apply to reproducing or transmitting the document in any form: 1) all copies or portions thereof must identify the document's IEEE project number and draft number, and must be accompanied by this entire notice in a prominent location; 2) no portion of this document may be redistributed in any modified or abridged form without the prior approval of the IEEE Standards Department.

Other entities seeking permission to reproduce this document, or any portion thereof, for standardization or other activities, must contact the IEEE Standards Department for the appropriate license.

Use of information contained in this unapproved draft is at your own risk.

IEEE Standards Department
Copyright and Permissions
445 Hoes Lane, P.O. Box 1331
Piscataway, NJ 08855-1331, USA
+1 (908) 562-3800
+1 (908) 562-1571 [FAX]

## B.1 C Language Definitions

### B.1.1 POSIX Symbols

Certain symbols in this annex are defined in headers. Some of those headers could also define symbols other than those defined by this standard, potentially conflicting with symbols used by the application. Also, this standard defines symbols that other standards do not permit to appear in those headers without some control on the visibility of those symbols.

Symbols called *feature test macros* are used to control the visibility of symbols that might be included in a header. Implementations, future versions of this standard, and other standards may define additional feature test macros. The `#define`s for feature test macros shall appear in the application source code before any `#include` of a header where a symbol should be visible to some, but not all, applications. If the definition of the macro does not precede the `#include`, the result is undefined.

Feature test macros shall begin with the underscore character (_) and an uppercase letter, or with two underscore characters.

Implementations may add symbols to the headers shown in Table B-1, provided the identifiers for those symbols begin with the corresponding reserved prefixes in Table B-1. Similarly, implementations may add symbols to the headers in Table B-1 that end in the string indicated as a reserved suffix as long as the reserved suffix is in that part of the name considered significant by the implementation. This shall be in addition to any reservations made in the C Standard {7}.

After the last inclusion of a given header, an application may use any of the symbol classes reserved in Table B-1 for its own purposes, as long as the requirements in the note to Table B-1 are satisfied, noting that the symbol declared in the header may become inaccessible.

Future revisions of this standard, and other POSIX standards, are likely to use symbols in these same reserved spaces.

In addition, implementations may add members to a structure or union without controlling the visibility of those members with a feature test macro, as long as a user-defined macro with the same name cannot interfere with the correct interpretation of the program.

A conforming POSIX. 2 application shall define the feature test macro in Table B-2. When an application includes a header and the _POSIX _C_SOURCE feature test macro is defined to be the value 1 or 2, the effect shall be the same as if _POSIX _SOURCE was defined as described in POSIX .1 {8}.

In addition, when the application includes any of the headers defined in this standard, and _POSIX _C_SOURCE is defined to be the value 2:

(1) All symbols defined in POSIX. 2 to appear when the header is included shall be made visible.

Copyright © 1991 IEEE. All rights reserved.
This is an unapproved IEEE Standards Draft, subject to change.