Index

/

/usr/include/X11/bitmaps, 9
/usr/lib/X11/app-defaults, 15

A

A, note, **4**
app-defaults, 15
application defaults, 15
application header file, **4**
application programmer, **2**
Arg, **16**
ArgList, **16**
argument lists, **16**
AsciiSink object, 90, **98**, 99
  class name, 98
  resources, 98, 107
AsciiSink.h, 98
asciiSinkObjectClass, 98
AsciiSinkP.h, 98
AsciiSrc object, 90, **95**, 99
  class name, 95
  resources, 96
AsciiSrc.h, 95
asciiSrcObjectClass, 95
AsciiSrcP.h, 95
AsciiText widget, **89**, 100
  class name, 90
  resources, 90
AsciiText.h, 89
AsciiTextP.h, 89
asciiTextWidgetClass, 89

B

bitmap conversions, **9**
BitmapFilePath, **9**
bitmapFilePath, **9**
Box widget, **112**
  class name, 113
  layout semantics, 114
  resources, 113, 132
Box.h, 113, 131
BoxP.h, 113
boxWidgetClass, 113
ButtonPress, 143

C

C, note, **4**
CallbackProc, **12**
callbacks, 12
chapter format, **4**
child, 2
class header file, **4**
class name, **4**
class, **2**, **4**
client, **2**
Command widget, **18**
  actions, 22
  class name, 18
  resources, 19
  translation bindings, 22
Command.h, 18
CommandP.h, 18
commandWidgetClass, 18
compiling applications, 14
conventions:
  chapter format, **4**
  used in manual, **3**
conversions, **8**
  AsciiType, 94, 97
  BackingStore, 61
  Bitmap, **9**
  ColorCursor, **9**
  Cursor, **9**
  Gravity, 133
  Justify, 21, 28, 40, 55, 71
  Orientation, 44, 114, 125
  Pixel, **9**
  ShapeStyle, 21, 41, 56, 72
  Widget, 117, 122
  XawTextEditType, 92, 96, 104
  XawTextResizeMode, 93, 102
  XawTextScrollMode, 93, 102
Core widget, 137
creating new widgets, **137**
creating widgets, **7**
cursor, 9

D

D, note, **4**
destroyCallback, **13**

Dialog widget, 112, **115**
  automatically created children, 118
  class name, 115
  constraint resources, 117
  layout semantics, 117
  resources, 115
  special considerations, 118
Dialog.h, 115
DialogP.h, 115
dialogWidgetClass, 115

E

events, 10
examples, 17

F

fallback resources, **6**
FindPosition, 110
float resources:
  setting, 47
FMT8BIT, 86
Form widget, 112, **119**
  class name, 119
  constraint resources, 121
  re-layout, 122
  resources, 120
Form.h, 119
FormP.h, 119
formWidgetClass, 119
fromHoriz, 117, 122
fromLeft, 118
fromVert, 117, 122
FullName, 2

G

geometry management, 112
Grip widget, 18, **23**
  actions, 25
  class name, 23
  GripAction routine, 25
  GripAction table, 25
  resources, 23
Grip.h, 23
GripAction, 128
GripCallData, 25
GripP.h, 23
gripWidgetClass, 23

H

horizDistance, 117, 122

I

initialization, **6**
input focus, **5**
Input Method, 83
input, **5**
instance, **2**
internationalization, 6
Intrinsic.h, 13
introduction, **1**

J

jumpProc, 45, **46**

K

KeyPress, 143

L

Label widget, 18, **25**
  class name, 25
  resources, 26
Label.h, 25
LabelP.h, 25
labelWidgetClass, 25
libICE, 14
libSM, 14
libX11, 14
libXaw, 14
libXext, 14
libXmu, 14
libXt, 14
linking applications, 14
List widget, 18, **28**
  actions, 31
  callbacks, 32
  class name, 28
  default translation table, 31
  resources, 29
List.h, 28
ListP.h, 28
listWidgetClass, 28

locale, 6

M

MenuButton widget, **68**
  actions, 72
  class name, 68
  resources, 69
MenuButton.h, 68
MenuButtonP.h, 68
menuButtonWidgetClass, 68
Menus, 59
  popup, 59
  pulldown, 59
  using, 59
method, **2**
MultiSink object, 90, 99
MultiSrc object, 90, 99

N

name:
  widget, **2**
notes, **4**

O

object, **2**

P

Paned widget, 112, **123**
  change height settings, 128
  class name, 123
  constraint resources, 126
  disable auto-reconfiguring, 129
  disable pane resizing, 128
  enable auto-reconfiguring, 129
  enable pane resizing, 128
  get height settings, 128
  getting the number of children, 129
  layout semantics, 126
  resources, 123
  using, 123
Paned.h, 123
PanedP.h, 123
panedWidgetClass, 123
Panner widget, 18, **33**
  actions, 36
  callbacks, 37
  class name, 33
  default translation table, 37
  resources, 34
Panner.h, 33
PannerP.h, 33
pannerWidgetClass, 33
parent, **2**
pixel, 9
Porthole widget, 112, **129**
  callbacks, 131
  class name, 129
  layout semantics, 131
  resources, 129
Porthole.h, 129
PortholeP.h, 129
portholeWidgetClass, 129

R

R, note, **4**
Radio button, 52
Radio groups, 52, 57
  one of many, 57
  zero or one of many, 57
radioData, 58
realizing widgets, **9**
Repeater widget, 18, **37**
  actions, 41
  class name, 37
  resources, 38
  translation bindings, 41
Repeater.h, 37
RepeaterP.h, 37
repeaterWidgetClass, 37
ReportProc, **37**, **131**
resource, **2**, 8, 14
rgb.txt, 9

S

Scrollbar widget, 18, **42**
  actions, 45
  callbacks, 46
  class name, 42
  default translation table, 45
  resources, 42
  setting thumb values, 46
Scrollbar.h, 42
ScrollbarP.h, 42
scrollbarWidgetClass, 42
ScrollProc, **46**
SetSelection, **107**
Simple widget, 18, **47**
  class name, 47
  resources, 47
simple widgets, 18

Simple.h, 47
SimpleMenP.h, 60
SimpleMenu widget, **60**
  actions, 62
  class name, 60
  default translations, 62
  MenuPopdown routine, 63
  positioning, **63**
  resources, 60
SimpleMenu.h, 60
simpleMenuWidgetClass, 60
SimpleP.h, 47
simpleWidgetClass, 47
Sme object, 59, **67**
  class name, 67
  Highlight method, 68
  Notify method, 68
  subclassing, 68
  Unhighlight method, 68
Sme.h, 67
SmeBSB object, 59, **64**
  class name, 64
  resources, 65
SmeBSB.h, 64
smeBSBObjectClass, 64
SmeBSBP.h, 64
SmeLine object, 59, **66**
  class name, 66
  resources, 66, 67
SmeLine.h, 66
smeLineObjectClass, 66
SmeLineP.h, 66
smeObjectClass, 67
SmeP.h, 67
string conversions, **8**
StringDefs.h, 13
StripCharP.h, 49
StripChart widget, 18, **49**
  class name, 49
  getting the value, 52
  getValue callback, **52**
  resources, 49
StripChart.h, 49
stripChartWidgetClass, 49
subclassing, **137**
superclass, **2**, 4

T

Text widget, 99, **100**
  actions, **77**
  class name, 100
  ConvertSelection, **106**
  customizing, **99**
  default key bindings, 74
  default translations, 84
  edit modes, 74
  file insertion, 76
  query replace, 75
  resources, 100
  search, 75
  Text Selections for Application Programmers, 83
  Text Selections for Users, 77
  User’s Guide to the Text widget, 74
Text.h, 100
TextP.h, 100
TextSink object, 99, **107**
  class name, 107
  ClearToBackground, **109**
  DisplayText, **108**
  FindDistance, **110**
  FindPosition, **109**
  GetCursorBounds, **111**
  InsertCursor, **108**
  MaxHeight, **111**
  MaxLines, **110**
  Resolve, **109**
  SetTabs, **111**
  subclassing, **107**
TextSink.h, 107
textSinkObjectClass, 107
TextSinkP.h, 107
TextSrc object, 99, **103**
  class name, 103
  Read, **104**
  Replace, **105**
  resources, 104
  Scan, **105**
  Search, **106**
  subclassing, **104**
TextSrc.h, 103
textSrcObjectClass, 103
TextSrcP.h, 103
textWidgetClass, 100
Toggle widget, 18, **52**
  actions, 56
  class name, 52
  default translation table, 56
  resources, 53
  used in radio groups, 52
Toggle.h, 52
ToggleP.h, 52
toggleWidgetClass, 52
toolkit initialization, **6**
Tree widget, 112, **131**
  class name, 131

constraint resources, 133
convenience routines, 134
layout semantics, 133
TreeP.h, 131
treeWidgetClass, 131
type conversions, **8**

U

underlying model, **3**
user, **2**
using widgets, **6**

V

vertDistance, 117, 122
Viewport widget, 112, **134**
class name, 134
layout semantics, 136
resources, 134
Viewport.h, 134
ViewportP.h, 134
viewportWidgetClass, 134

W

widget class, **3**
widget creation, **7**
widget programmer, **3**
widget, **3**
widgetClass, 137
Window widget, 137
WrapMode, 94, 103
writing applications, 13

X

X11/Intrinsic.h, 13
X11/Xaw/Command.h, 13
X11/Xaw/Label.h, 13
X11/Xaw/Template.c, 138, 141
X11/Xaw/Template.h, 138
X11/Xaw/TemplateP.h, 138, 140
X11/Xlib.h, 13
XawAsciiSave, **97**, 98
XawAsciiSaveAsFile, **98**
XawAsciiSourceChanged, **98**
XawAsciiSourceFreeString, **97**, 119
XawChain, 118, 122
XawChainBottom, 118, 122
XawChainLeft, 118, 122
XawChainRight, 118, 122
XawChainTop, 118, 122
XawDialogAddButton, **119**
XawDialogGetValueString, **118**
XawEdgeType, 117, 121
XawEditDone, 87, 105
XawEditError, 87, 105
XawFormDoLayout, **122**
XawGripCallData, **25**
XawGripCallDataRec, **25**
XawListChange, **32**, 33
XawListHighlight, **33**
XawListReturnStruct, **32**, 33
XawListShowCurrent, **33**
XawListUnhighlight, **33**
XawPanedAllowResize, **128**
XawPanedGetMinMax, **128**
XawPanedGetNumSub, **129**
XawPanedSetMinMax, **128**
XawPanedSetRefigureMode, **129**
XawPositionError, 87, 105
XawPositionSimpleMenu, **63**, 64
XawRubber, 117, 118, 121, 122
XawScrollbarSetThumb, **46**
XawScrollbarThumb, 47
XawsdLeft, 105, 106
XawsdRight, 105, 106
XawselectAll, 83
XawselectChar, 83
XawselectLine, 83
XawselectNull, 83
XawselectParagraph, 83
XawselectPosition, 83
XawselectWord, 83
XawSimpleMenuAddGlobalActions, **64**
XawSimpleMenuClearActiveEntry, **64**
XawSimpleMenuGetActiveEntry, **64**
XawstAll, 105
XawstEOL, 105
XawstParagraph, 105
XawstPositions, 105
XawstWhiteSpace, 105
XawtextAppend, 92, 96, 104
XawTextBlock, **85**
XawTextBlockPtr, 85
XawTextDisableRedisplay, **88**
XawTextDisplay, **88**
XawTextDisplayCaret, **89**
XawtextEdit, 92, 96, 104
XawTextEnableRedisplay, **87**
XawTextGetInsertionPoint, **89**
XawTextGetSelectionPos, **86**
XawTextGetSource, **89**
XawTextInvalidate, **87**
XawTextPosition, **85**

XawtextRead, 92, 96, 104
XawTextReplace, 74, **86**
XawtextResizeBoth, 93, 102
XawtextResizeHeight, 93, 102
XawtextResizeNever, 93, 102
XawtextResizeWidth, 93, 102
XawtextScrollAlways, 93, 102
XawtextScrollNever, 93, 102
XawtextScrollWhenNeeded, 93, 102
XawTextSearch, **87**
XawTextSearchError, 106
XawTextSetInsertionPoint, **88**
XawTextSetSelection, **86**
XawTextSetSelectionArray, 83, **88**
XawTextSetSource, **89**
XawTextSinkClearToBackground, 108
XawTextSinkDisplayText, 108
XawTextSinkFindDistance, 108
XawTextSinkFindPosition, 108
XawTextSinkGetCursorBounds, 108
XawTextSinkInsertCursor, 108
XawTextSinkMaxHeight, 108
XawTextSinkMaxLines, 108
XawTextSinkResolve, 108
XawTextSinkSetTabs, 108
XawTextSourceConvertSelection, 104
XawTextSourceRead, 104
XawTextSourceReplace, 104
XawTextSourceScan, 104
XawTextSourceSearch, 104
XawTextSourceSetSelection, 104
XawTextTopPosition, 88
XawTextUnsetSelection, **86**
XawtextWrapLine, 94, 103
XawtextWrapNever, 94, 103
XawtextWrapWord, 94, 103
XawToggleChangeRadioGroup, **58**
XawToggleGetCurrent, **58**
XawToggleSetCurrent, **58**
XawToggleUnsetCurrent, **58**
XawTreeForceLayout, **134**
XawWMProtocols, 82
XAW_LIST_NONE, 33
xrdb, 15
XrmParseCommand, 7
XtAddCallback, 12, **13**, 14
XtAddCallbacks, 12
XtAppInitialize, **6**, 10, 13
XtAppMainLoop, **10**, 14
XtCallbackList, **12**
XtCallbackProc, 12
XtCallbackRec, **12**
XtCreateManagedWidget, **7**, 14
XtCreateWidget, 11, 12, 13
XtDefaultBackground, 8, 9
XtDefaultForeground, 8, 9
XtDestroyWidget, **11**
XtError, 7
XtGetApplicationResources, 16
XtGetValues, **11**, 12, 144
XtInheritClearToBackground, 108, 109
XtInheritConvertSelection, 104
XtInheritDisplayText, 108
XtInheritFindDistance, 108
XtInheritFindPosition, 108
XtInheritGetCursorBounds, 108
XtInheritInsertCursor, 108
XtInheritMaxHeight, 108
XtInheritMaxLines, 108
XtInheritRead, 104
XtInheritReplace, 104
XtInheritResolve, 108
XtInheritScan, 104
XtInheritSearch, 104
XtInheritSetSelection, 104
XtInheritSetTabs, 108
XtManageChildren, **11**
XtMapWidget, **10**
XtMoveWidget, 112
XtN, **13**
XtNameToWidget, 118, 136
XtNcallback, 14
XtNinput, **5**
XtNumber, 16, 17
XtorientHorizontal, 44, 114, **115**, 125
XtorientVertical, 44, **114**, 125
XtRealizeWidget, 7, **9**, 10, 14
XtResizeWidget, 112
XtSetArg, **16**, 17
XtSetLanguageProc, **6**
XtSetMappedWhenManaged, **10**
XtSetValues, **12**, 112, 138, 140
XtWindow, 144

_

_in_out, **3**
_return, **3**